INTERSPIRO

QS II S-FACE MASK

AMBIENT AIR VERSION

WITH S-BREATHING VALVE

❶ Outstanding breathing valve performance
•→ **Very low breathing resistance**

❷ Breathing valve is activated from inner mask
•→ **Instantaneous response to workload changes**

❸ Ambient air hatch for standby use
•→ **Extended duration time**

❹ Breathing valve has a positive lock
•→ **Secure connection of breathing valve**

❺ Silent operational mode
•→ **Communicate without noise interference**

❻ Mask and Breathing valve in a compact design
•→ **No protruding parts**

❼ Fits spectacles and communication devices
•→ **Flexibility for different users and purposes**

❽ The mask is available in three different sizes
•→ **Excellent fit for all face shapes and sizes**

Merkez: İkitelli OSB Aykosan Sanayi 2.Kısım
5.Ada C Blok 34490 Başakşehir / İSTANBUL
Tel: +90 (212) 671 28 00 Pbx
Gsm: +90 (533) 395 06 98-99
Faks: +90 (212) 671 99 27

www.kivancgroup.com / **info@kivancgroup.com**

KIVANÇ Group

QS II S-FACE MASK
WITH S-BREATHING VALVE

REFERS TO PRODUCT(-S) WITH PART NO.(-S)
31820-series

AMBIENT AIR VERSION

S-FACE MASK is comfortable and reliable, designed with Interspiros outstanding safety pedigree and innovative approach.

The inner mask separates inhaled and exhaled air to minimize the danger of breathing exhaled carbon dioxide. An ambient air hatch with double action release mechanism enables the use of ambient air while in stand-by.

S-BREATHING VALVE is a positive pressure valve with a secure connection to the face mask. The design of the demand valve supplies air only while inhaling, with instantaneous response to workload differences. Positive pressure is activated with a one-hand push on the exhalation valve cover.

Breathing apparatus from Interspiro is an investment with a long service life, when properly maintained. To simplify service and to obtain maximum product performance we recommend using our service kits, containing original spare parts necessary for preventive maintenance.

Interspiro offers training courses for users who perform day-to-day service work, as well as training for service personnel performing full maintenance programmes.

For more information about the QS II product range and our other breathing protection products please visit us on the Internet: www.interspiro.com

STANDARDS AND APPROVALS
- EN 136 Class 3
- EN 137 (Complete Apparatus)
- CE 89/686/EEC

MATERIALS

Mask Body	Natural rubber or Silicone
Visor	Heat resistant Polycarbonate Scratch resistant and anti-fog coating
Breathing Valve	Heat resistant Polyamid

DIMENSIONS AND WEIGHT

Dimensions (h x w x d)	250 x 160 x 150 mm
Weight	0.83 kg

PERFORMANCE

Flow rate with preserved positive pressure

Inner/outer mask	>450/>650 l/min.
Medium pressure range	5–11 bar

CONNECTION TO BREATHING HOSE
- **M16 x 1**

OPTIONS
- Hair net
- By-pass valve
- Radio communication
- Spectacle kit

Merkez: İkitelli OSB Aykosan Sanayi 2.Kısım
5.Ada C Blok 34490 Başakşehir / İSTANBUL
Tel: +90 (212) 671 28 00 Pbx
Gsm: +90 (533) 395 06 98-99
Faks: +90 (212) 671 99 27
www.kivancgroup.com / **info@kivancgroup.com**